


SINGLE PHASE BRIDGE

Power Modules

Features

- Universal, 3 way terminals:
push-on, wrap around or solder
- High thermal conductivity package,
electrically insulated case
- Center hole fixing
- Excellent power/volume ratio
- UL E300359 approved 
- Nickel plated terminals solderable using Lead-Free solder;
Solder Alloy Sn/Ag/Cu (SAC305); Solder temperature 260-275°C
- RoHS compliant

25 A
35 A

Description

A range of extremely compact, encapsulated single phase bridge rectifiers offering efficient and reliable operation. They are intended for use in general purpose and instrumentation applications.

Major Ratings and Characteristics

| Parameters | 26MB-A | 36MB-A | Units |
|------------------|--------------|--------|------------------|
| I_O | 25 | 35 | A |
| @ T_C | 70 | 55 | °C |
| I_{FSM} @ 50Hz | 400 | 475 | A |
| @ 60Hz | 420 | 500 | A |
| I^2t @ 50Hz | 790 | 1130 | A ² s |
| @ 60Hz | 725 | 1030 | A ² s |
| V_{RRM} range | 1400 to 1600 | | V |
| T_J | -55 to 150 | | °C |

ELECTRICAL SPECIFICATIONS

Voltage Ratings

| Type number | Voltage Code | V_{RRM} , maximum repetitive peak reverse voltage V | V_{RSM} , maximum non-repetitive peak rev. voltage V | I_{RRM} max. @ T_J max. mA |
|-------------|--------------|--|---|--------------------------------------|
| 26MB..A | 140 | 1400 | 1500 | 2 |
| 36MB..A | 160 | 1600 | 1700 | |

Forward Conduction

| Parameters | 26MB-A | 36MB-A | Units | Conditions |
|--|--------|--------|--------------------|--|
| I_O Maximum DC output current @ Case temperature | 25 | 35 | A | Resistive or inductive load |
| | 20 | 28 | A | Capacitive load |
| | 65 | 60 | °C | |
| I_{FSM} Maximum peak, one-cycle non-repetitive forward current | 400 | 475 | A | t = 10ms No voltage reappplied |
| | 420 | 500 | | t = 8.3ms |
| | 335 | 400 | | t = 10ms 100% V_{RRM} |
| | 350 | 420 | | t = 8.3ms reappplied |
| I^2t Maximum I^2t for fusing | 790 | 1130 | A ² s | t = 10ms No voltage reappplied |
| | 725 | 1030 | | t = 8.3ms |
| | 560 | 800 | | t = 10ms 100% V_{RRM} |
| | 512 | 730 | | t = 8.3ms reappplied |
| $I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing | 5.6 | 11.3 | KA ² √s | I^2t for time $t_x = I^2\sqrt{t_x} \sqrt{t_x}$; $0.1 \leq t_x \leq 10ms, V_{RRM} = 0V$ |
| $V_{F(TO)1}$ Low-level of threshold voltage | 0.70 | 0.74 | V | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, @ T_J max. |
| $V_{F(TO)2}$ High-level of threshold voltage | 0.75 | 0.79 | V | $(I > \pi \times I_{F(AV)})$, @ T_J max. |
| r_{t1} Low-level forward slope resistance | 7.0 | 5.5 | mΩ | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, @ T_J max. |
| r_{t2} High-level forward slope resistance | 6.4 | 5.2 | | $(I > \pi \times I_{F(AV)})$, @ T_J max. |
| V_{FM} Maximum forward voltage drop | 1.25 | 1.3 | V | $T_J = 25^\circ C, I_{FM} = 40A_{PK}$ (26MB) |
| | | | | $T_J = 25^\circ C, I_{FM} = 55A_{PK}$ (36MB) |
| I_{RRM} Max. DC reverse current | 10 | 10 | μA | $T_J = 25^\circ C$, per diode at V_{RRM} |
| V_{INS} RMS isolation voltage base plate | 2700 | 2700 | V | f = 50 Hz, t = 1s |

Thermal and Mechanical Specifications

| Parameters | 26MB-A | 36MB-A | Units | Conditions |
|--|---------------|--------|-------|--|
| T_J Junction temperature range | -55 to 150 °C | | | |
| T_{stg} Storage temperature range | -55 to 150 °C | | | |
| R_{thJC} Max. thermal resistance junction to case | 1.7 | 1.35 | K/W | Per bridge |
| R_{thCS} Max. thermal resistance, case to heatsink | 0.2 | | K/W | Mounting surface, smooth, flat and greased |
| wt Approximate weight | 20 | | g | |
| T Mounting Torque ±10% | 2.0 | | Nm | Bridge to heatsink |

Ordering Information Table

| Device Code | 36 | MB | 160 | A |
|--|----|----|-----|---|
| | ① | ② | ③ | ④ |
| <p>1 - Current rating code: 26 = 25A (Avg) 36 = 35A (Avg)</p> <p>2 - Circuit configuration: MB = Single phase european coding</p> <p>3 - Voltage code: MB series = code x 10 = V_{RRM}</p> <p>4 - Diode bridge rectifier: A = 26MB, 36MB Series</p> | | | | |

Outline Table

0.8 (.03) 6.3 (.25)

10.5 (.41) 20.3 (.80)

21.5 (0.85) 9.5 (0.37) 28.5 (1.12)

5 (0.2) *12.7 (0.5)

28.5 (1.12)

Suggested plugging force:
200 N max; axially applied to faston terminals

Not To Scale

All dimensions in millimetres (inches)




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Forward Voltage Drop Characteristics
Maximum Allowable Ambient Te




Fig. 3 - Total Power Loss Characteristics




Fig. 4 - Maximum Non-Repetitive Surge Current




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Current Ratings Characteristics




Fig. 7 - Forward Voltage Drop Characteristics




Fig. 3 - Total Power Loss Characteristics




Fig. 9 - Maximum Non-Repetitive Surge Current




Fig. 10 - Maximum Non-Repetitive Surge Current

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial and Consumer Level.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
09/06



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.